



Product Service

Attestation of Conformity

No. N8A 076777 0054 Rev. 00

Holder of Certificate: **Shenzhen Sinexcel Electric Co., Ltd**
Building 6, BaiWangXin
High-tech Industrial Park, Nanshan District
518055 Shenzhen City
PEOPLE'S REPUBLIC OF CHINA

Product: **Electric vehicle charging station**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105223034501

Date, 2022-11-22

(Glenn Liu)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 076777 0054 Rev. 00

Model(s): **SEA230/32M-E-S, SEA230/32M-E-C**
SEA 230 / 32 M - E - S/C
 I II III IV V VI
I: Product series
II: Rated system voltage
 230: 230V
III: Rated system current
 32: 32A
IV: Product Series Name
 M: Mira
V: certification type
 E: CE
 A: RCM
VI: system type
 S: socket
 C: cable

Parameters:

Rated input Voltage (V): AC230V, 50/60Hz, 1P+N+PE
 Rated input current(A): Max. 32 A for SEA230/32M-E-S
 Max. 32 A for SEA230/32M-E-C;
 Output voltage (V): AC230V, 50/60Hz, 1P+N+PE
 Output current (A): Max. 32 A for SEA230/32M-E-S
 Max. 32 A for SEA230/32M-E-C;
 Output power(kW): Max. 7 kW for SEA230/32M-E-S
 Max. 7 kW for SEA230/32M-E-C;
 Protection class: Class I
 Degree of protection: IP55 for SEA230/32M-E-S
 IP65 for SEA230/32M-E-C
 Pollution degree: 3
 Remark: Insulation between communication circuit and HV is reinforce insulation.

Tested according to: EN IEC 61851-1:2019